



1120 De L'Express  
Terrebonne, Quebec  
J6W 6K9

## Application Guide - UV Screen Printing

	A40	ABOUND	CD	CTR	Excel Plus R	ES Vinyl	FL-1	Seriglass	TF2
<b>ABS</b>	X	X			X*		X*		
<b>Acrylic</b>	X	X*			X*		X*		X*
<b>Corrugated Propylene (Corona Treated)</b>	X	X			X**		X**		
<b>Glass</b>								X	
<b>Metal - Acrylic Coated</b>	X				X**		X**		
<b>Paper / Cardboard</b>	X	X			X		X		
<b>PET / PETE / PETG</b>	X			X	X*		X*		X
<b>Polycarbonate</b>	X*	X*			X*		X*		X*
<b>Polyester</b>	X*	X*			X*		X*		X*
<b>Polyethylene Containers</b>	X			X	X**		X**		
<b>Polyolefins</b>	X*	X*			X**		X**		
<b>Polypropylene Synthetic Paper (MXM)</b>	X	X			X*		X*		
<b>Polystyrene</b>	X	X			X		X		X
<b>Compact discs</b>		X	X						
<b>Tyvek</b>	X*	X*			X*	X	X*		
<b>Vinyl - Auto Adhesive</b>	X	X			X	X	X		
<b>Vinyl - Banner</b>	X*	X*			X	X	X		
<b>Vinyl - Rigid</b>	X	X			X*		X*		X
<b>Vinyl - Static Cling</b>						X			

\* Some materials

\*\* Need catalyst

\*\*\* Adhesion might be impacted by climate conditions

Due to the unlimited types and nature of the substrates presently used in screen printing, some of which could be beyond the control of our laboratory, we strongly recommend that complete tests of adherence and other particular requirements to be performed by the end user prior to production. Please contact our technical laboratory for any questions you might have regarding ARIA products. Our specialists will assist you to select the best ink for your application or will develop the product which will perfectly meet your requirements.